

Section 21 Town 7 Range 7

Sept. 1st + 2nd 1927

I commenced a Survey of Section 21, T. 7, R. 7  
for Walter Pool et al.  
I began survey from the Southwest corner  
stone of Sect. 21 - T. 7 N. - R. 7 W and ran  
survey line to NW corner of same both  
stones being found to be in proper location  
I next located the NW corner and the  
West corner of the S.W. 1/4 was requested  
Howard R. Forbes Duly Sworn before  
starting survey  
C. B. J  
H. W. Clogston & Dist. Surveyor.  
Herbert Linder Forbes  
Surveyor Greene County.

Albert Davis  
1/4 Sec Pool

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
N-2°-30'W	SW Cor	79.98ch To NW-Corner	
	SW Cor	19.995ch to W 1/4 of SW	
	SW Cor	39.99ch to W 1/4 corner	

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
W 1/4 Sect. 21	Large stone 10" x 12" x 20"	x in center	Walnut	26"	S 80° 00' W	99.25'	
			Per cimon	14	S 71° 00' E	65.6'	
W 1/4 SW Sect. 21	lime stone 5" x 6" x 22"	marked hole in center	Set stone on end water oak	14	North	130.45'	
Found low SW 1/4 Sect. 21	Sandstone	Hole in center	Willd Goose Plump	8"	S W	23.45'	
			ELM	12"	N 38° 45' E	28.5'	